







# Nosilnosti bremenskih jeklenih vrvi

## Working load limits for wire ropes

EN 13414-1

									
Kot/Angle	0°	0°	0°-45°	45°-60°	0°-45°	45°-60°	0°-45°	45°-60°	0°
F	1	0.8	1.4	1	1.12	0.8	2.1	1.5	1.6
Premer/Diameter (mm)									
6	380	300	530	380	430	300	800	570	610
8	700	560	950	700	780	560	1500	1050	1100
10	1050	840	1500	1050	1100	840	2250	1600	1700
12	1550	1240	2120	1550	1700	1240	3300	2300	2500
14	2120	1600	3000	2120	2300	1600	4350	3150	3300
16	2700	2100	3850	2700	3000	2100	5650	4200	4350
18	3400	2700	4800	3400	3800	2700	7200	5200	5650
20	4350	3400	6000	4350	4800	3400	9000	6500	6900
22	5200	4100	7200	5200	5800	4100	11000	7800	8400
24	6300	5000	8800	6300	7000	5000	13500	9400	10000
26	7200	5700	10000	7200	8000	5700	15000	11000	11800
28	8400	6700	11800	8400	9400	6700	18000	12500	13500
32	11000	8800	15000	11000	12300	8800	23500	16500	18000
36	14000	11200	19000	14000	15600	11200	29000	21000	22500
40	17000	13600	23500	17000	19000	13600	36000	26000	28000
52	29000	23200	40000	29000	32400	23200	62000	44000	47000
56	33500	26800	47000	33500	37500	26800	71000	50000	54000
60	39000	31200	54000	39000	43600	31200	81000	58000	63000

Pred uporabo bremenskih jeklenih vrvi se morate prepričati ali jih smete uporabljati.

Na željo kupca se izdelajo jeklene vrvi z večjo nosilnostjo.

Wire ropes could be made for high loads by request.