

# Povezovalne verige

## Lashing chains



**Veriga za povezovanje tovora z zategom tip RLSP**

Lashing chain with binder type RLSP

| Oznaka   | Premer       | Nosilnost               | *01 | *02 | *03 | *04 | *05 |
|----------|--------------|-------------------------|-----|-----|-----|-----|-----|
| Art. No. | Diametr (mm) | Working load limit (kg) | 2 m | 2 m | 3 m | 4 m | 5 m |
| 8606**   | 6            | 2000                    |     |     |     |     |     |
| 8608**   | 8            | 4000                    |     |     |     |     |     |
| 8610**   | 10           | 6400                    |     |     |     |     |     |
| 8613**   | 13           | 10000                   |     |     |     |     |     |

**Veriga za povezovanje tovora z matico tip SSP**

Lashing chain with turnbuckle type SSP

| Oznaka   | Premer       | Nosilnost               | *01 | *02 | *03 | *04 | *05 |
|----------|--------------|-------------------------|-----|-----|-----|-----|-----|
| Art. No. | Diametr (mm) | Working load limit (kg) | 2 m | 2 m | 3 m | 4 m | 5 m |
| 8506**   | 6            | 2000                    |     |     |     |     |     |
| 8508**   | 8            | 4000                    |     |     |     |     |     |
| 8510**   | 10           | 6400                    |     |     |     |     |     |
| 8513**   | 13           | 10000                   |     |     |     |     |     |
| 8516**   | 16           | 16000                   |     |     |     |     |     |

**Zateg tip LSP**


Load binder type LSP



| Velikost, premer verige   | Dovoljena obremenitev pri povezovanju | Dolžina ročice   | Dolžina zatega | Teža                | Oznaka   |
|---------------------------|---------------------------------------|------------------|----------------|---------------------|----------|
| Nominal size = chain dia. | Ultimate strenght kg                  | Handle length mm | Take- up mm    | Weight per piece kg | Art. No. |
| 8 – 10                    | 8500                                  | 406              | 114            | 3,7                 | 6450010  |
| 10 – 13                   | 14700                                 | 470              | 114            | 5,1                 | 6450013  |

**Natezna matica z naperjalcem tip RLSP za povezovanje**

Ratchet type load binder type RLSP




| Velikost, premer verige   | Dovoljena obremenitev pri povezovanju | Dolžina ročice   | Dolžina  | Dolžina  | Dolžina zatega | Teža             | Teža             | Oznaka brez kavljja | Oznaka s kavljji |
|---------------------------|---------------------------------------|------------------|----------|----------|----------------|------------------|------------------|---------------------|------------------|
| Nominal size = chain diam | Ultimat-estrength kg                  | Handle length mm | Length I | Length I | Take- up mm    | Weight per piece | Weight per piece | Art. No.            | Art. No.         |
|                           |                                       |                  | min mm   | max mm   |                | Without hooks    | With hooks       | Without hooks       | With hooks       |
| 8 – 10                    | 8500                                  | 355              | 362      | 565      | 203            | 3,4              | 4,7              | 64052008            | 64053008         |
| 10 – 13                   | 14700                                 | 355              | 362      | 565      | 203            | 3,4              | 5,7              | 64052010            | 64053010         |
| 13                        | 20500                                 | 355              | 362      | 565      | 203            | 3,8              | -                | 64052013            | -                |

# Povezovalne verige

## Lashing chains

### Verižni napenjalec tip SSP za povezovanje


### Clevis type turnbuckle type SSP for lashing



| Velikost, premer verige  | Dovoljena obremenitev pri povezovanju | Nosilnost                       | Dolžina  | Dolžina  | Dolžina zatega | Teža                | Oznaka   |
|--------------------------|---------------------------------------|---------------------------------|----------|----------|----------------|---------------------|----------|
| Nominal size = chain dia | Tension load (lashing) daN (kp)       | Working load limit (lifting) kg | Length I | Length I | Take-up mm     | Weight per piece kg | Art. No. |
|                          |                                       |                                 | min mm   | max mm   |                |                     |          |
| 8-8                      | 4000                                  | 2000                            | 320      | 460      | 140            | 1,8                 | 64050008 |
| 10-8                     | 6400                                  | 3200                            | 450      | 680      | 230            | 3,3                 | 64050010 |
| 13-8                     | 10000                                 | 5000                            | 530      | 800      | 270            | 6,2                 | 64050013 |
| 16-8                     | 16000                                 | 8000                            | 600      | 900      | 350            | 12,5                | 64050016 |

### Natezna matica z napenjalcem tip RSP za povezovanje

### Ratchet type turnbuckle type RSP for lashing



| Velikost, premer verige  | Dovoljena obremenitev pri povezovanju | Nosilnost                       | Dolžina  | Dolžina  | Dolžina zatega | Teža                | Oznaka   |
|--------------------------|---------------------------------------|---------------------------------|----------|----------|----------------|---------------------|----------|
| Nominal size = chain dia | Tension load (lashing) daN (kp)       | Working load limit (lifting) kg | Length I | Length I | Take-up mm     | Weight per piece kg | Art. No. |
|                          |                                       |                                 | min mm   | max mm   |                |                     |          |
| 8-8                      | 4000                                  | 2000                            | 320      | 460      | 140            | 2,9                 | 64051008 |
| 10-8                     | 6400                                  | 3200                            | 450      | 680      | 230            | 4,3                 | 64051010 |
| 13-8                     | 10000                                 | 5000                            | 530      | 800      | 270            | 7,3                 | 64051013 |